




LOBO® SUPER SWAGED®

Extra High Strength Mainlines

Weights and Breaking Loads

Diameter inches (mm)	Rope Construction	Approx. Weight lbs/ft (kg/m)	Nominal Breaking Load tons (kN)
1/2 (13)	6x26 RRL Super Swaged	0.63 (0.94)	17.4 (155)
9/16 (14)	6x26 RRL Super Swaged	0.78 (1.16)	21.8 (194)
5/8 (16)	6x26 RRL Super Swaged	0.98 (1.46)	27.4 (244)
3/4 (19)	6x26 RRL Super Swaged	1.40 (2.08)	39.3 (350)
7/8 (22)	6x26 RRL Super Swaged	1.88 (2.80)	52.7 (469)




Breaking load values are subject to a minus tolerance of 2.5%.

CUSHION™ 6

Helicopter Logging Ropes

Weights and Breaking Loads

Diameter inches (mm)	Rope Construction	Approx. Weight lbs/ft (kg/m)	Nominal Breaking Load tons (kN)
1/2 (13)	6x26 Gd.130 IWRC Cushion Rope	0.47 (0.70)	14.1 (125)
9/16 (14)	6x26 Gd.130 IWRC Cushion Rope	0.60 (0.89)	17.6 (157)
5/8 (16)	6x26 Gd.130 IWRC Cushion Rope	0.75 (1.12)	22.0 (196)




Breaking load values are subject to a minus tolerance of 2.5%.

TIMBERFLEX® 6HS

High Strength Logging Ropes

Weights and Breaking Loads

Diameter inches (mm)	Rope Construction	Approx. Weight lbs/ft (kg/m)	Nominal Breaking Load tons (kN)
7/16 (11)	6x26 RRL Gd.130 IWRC	0.35 (0.52)	10.7 (95)
1/2 (13)	6x26 RRL Gd.130 IWRC	0.46 (0.68)	14.1 (125)
9/16 (14)	6x26 RRL Gd.130 IWRC	0.58 (0.86)	17.6 (157)
5/8 (16)	6x26 RRL Gd.130 IWRC	0.72 (1.07)	22.0 (196)



Breaking load values are subject to a minus tolerance of 2.5%.



Wire Rope Industries Ltd.
5501 Trans Canada Highway
Pointe Claire, Quebec
Canada H9R 1B7
Tel: (1-514-697-9711
www.wirerope.com



SERVICE REPRESENTATIVE