


POWER-LOC™ FLC
Full Lock Coil Hoisting and Sinking Ropes

Weights and Breaking Loads

Diameter inches (mm)	Approx. Weight lbs/ft (kg/m)	Nominal Breaking Load	
		HS lbs (kN)	EHS lbs (kN)
5/8 (15.9)	0.88 (1.31)	47 000 (209)	51 700 (230)
11/16 (17.5)	1.10 (1.64)	58 200 (259)	64 020 (285)
3/4 (19.1)	1.31 (1.95)	69 400 (309)	76 340 (340)
13/16 (20.6)	1.58 (2.35)	80 600 (359)	88 660 (395)
7/8 (22.2)	1.85 (2.75)	94 000 (418)	103 400 (460)
15/16 (23.8)	2.12 (3.16)	107 600 (479)	118 360 (527)
1 (25.4)	2.45 (3.65)	123 200 (549)	135 630 (604)
1-1/16 (27.0)	2.77 (4.12)	138 200 (615)	152 020 (677)
1-1/18 (28.6)	3.08 (4.58)	156 800 (698)	172 480 (768)
1-3/16 (30.2)	3.41 (5.08)	174 800 (778)	192 280 (856)
1-1/4 (31.8)	3.75 (5.58)	192 600 (857)	211 860 (943)
1-5/16 (33.3)	4.13 (6.15)	212 800 (947)	234 080 (1 042)
1-3/8 (34.9)	4.53 (6.74)	233 000 (1 037)	256 300 (1 141)
1-7/16 (36.5)	4.95 (7.37)	255 400 (1 137)	280 940 (1 250)
1-1/2 (38.1)	5.40 (8.04)	277 800 (1 236)	305 580 (1 360)
1-9/16 (39.7)	5.74 (8.54)	300 200 (1 336)	330 220 (1 470)
1-5/8 (41.3)	6.24 (9.29)	324 800 (1 446)	357 280 (1 590)
1-11/16 (42.9)	6.75 (10.05)	351 600 (1 565)	386 760 (1 721)
1-3/4 (44.5)	7.29 (10.85)	376 400 (1 675)	414 040 (1 843)
1-13/16 (46.0)	7.84 (11.67)	405 400 (1 804)	445 940 (1 985)
1-7/8 (47.6)	8.46 (12.59)	432 400 (1 925)	475 640 (2 117)
1-15/16 (49.2)	9.06 (13.49)	462 000 (2 056)	508 200 (2 262)
2 (50.8)	9.67 (14.39)	492 800 (2 193)	542 080 (2 413)
2-1/16 (52.4)	10.28 (15.30)	524 200 (2 333)	576 620 (2 567)
2-1/8 (54.0)	10.86 (16.17)	555 600 (2 473)	611 160 (2 720)

Breaking load values are subject to a minus tolerance of 5%.




POWER-LOC™ HLC
Half Lock Coil Guide and Rubbing Ropes

Weights and Breaking Loads

Diameter inches (mm)	Approx. Weight lbs/ft (kg/m)	Nominal Breaking Load	
		65 Long Tons/in ² - lbs (980 Mpa) - (kN)	70 Long Tons/in ² - lbs (1080 Mpa) - (kN)
1-1/2 (38.1)	5.46 (8.13)	195 600 (871)	215 500 (959)
1-5/8 (41.3)	6.42 (9.56)	229 600 (1 022)	252 900 (1 126)
1-3/4 (44.5)	7.45 (11.09)	266 300 (1 185)	293 400 (1 306)
1-7/8 (47.7)	8.55 (12.73)	305 700 (1 361)	336 800 (1 499)
2 (50.9)	9.73 (14.48)	347 800 (1 548)	383 200 (1 706)

Breaking load values are subject to a minus tolerance of 5%.



Wire Rope Industries Ltd.
5501 Trans Canada Highway
Pointe Claire, Quebec
Canada H9R 1B7
Tel: (1)-514-697-9711
www.wirerope.com



SERVICE REPRESENTATIVE